



# SAFETY DATA SHEET

Issuing Date: 23-Jan-2024

Revision Date: 23-Jan-2024

Print Date: 23-Jan-2024

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: WCS007UZ

Product Name: High Gloss Black Ura-Zen DTM-EX

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200  
Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Flammable Liquids	Category 2

### Label Elements

### Emergency Overview

**DANGER**

### Hazard Statements

Harmful if swallowed  
harmful if inhaled  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area

Wear eye/face protection  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
 Store in accordance with local regulations

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

- Harmful to aquatic life with long lasting effects
- Toxic to aquatic life

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Contains a known or suspected carcinogen**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
METHYL AMYL KETONE	110-43-0	10% - 20%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
BUTYL ACETATE	123-86-4	5% - 10%	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>
METHYL ETHYL KETONE	78-93-3	5% - 10%	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>
ZINC PHOSPHATE	7779-90-0	1% - 5%	N/A	N/A
CARBON BLACK	1333-86-4	1% - 5%	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup>
2-ETHYL HEXYL ACETATE	103-09-3	1% - 5%	N/A	N/A
ACETYLACETONE	123-54-6	1% - 5%	TWA: 25 ppm S*	N/A
TITANIUM DIOXIDE	13463-67-7	1% - 5%	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
ISOPARAFFINIC HYDROCARBON	64742-48-9	0% - 1%	N/A	N/A
LIGHT STABILIZER	41556-26-7	0% - 1%	N/A	N/A
LIGHT AROMATIC NAPHTHA	64742-95-6	0% - 1%	N/A	N/A
ETHYL ALCOHOL	64-17-5	0% - 1%	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>

### 4. FIRST AID MEASURES

**First Aid Measures**

---

<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash skin with soap and water.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water.
<b>Most important symptoms and effects, both acute and delayed</b>	
<b>Most Important Symptoms and Effects</b>	No information available.
<b>Indication of any immediate medical attention and special treatment needed</b>	
<b>Notes to physician</b>	Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

### Specific hazards arising from the chemical

Extremely flammable.

### Explosion Data

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Use personal protective equipment as required. Remove all sources of ignition. Avoid breathing vapors or mists. Ventilate the area.

### Environmental Precautions

**Environmental Precautions** Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep away from heat, sparks and flame.

**Incompatible Products** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
BUTYL ACETATE 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
METHYL ETHYL KETONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
ACETYLACETONE 123-54-6	TWA: 25 ppm S*	N/A	
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
ETHYL ALCOHOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>

NIOSH IDLH: Immediately Dangerous to Life or Health

**Exposure controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** If splashes are likely to occur, wear safety glasses with side-shields.

**Skin and Body Protection** Chemical resistant apron.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available

<b>pH</b>	No data available	<b>Flash Point</b>	16 °F / -9 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	175 °F / 79 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	1.05
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	8.70
		<b>EPA VOC (lb/gal)</b>	3.55
<b>Flammability Limits in Air</b>			
Upper	0.03 %		
Lower	0.01 %		

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Conditions to Avoid

Extremes of temperature and direct sunlight.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit )	2000 - 4000 ppm ( Rat ) 6 h
BUTYL ACETATE 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 0.74 mg/L ( Rat ) 4 h
METHYL ETHYL KETONE 78-93-3	= 2483 mg/kg ( Rat )	= 5000 mg/kg ( Rabbit )	= 11700 ppm ( Rat ) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg ( Rat )	N/A	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
ACETYLACETONE 123-54-6	= 570 mg/kg ( Rat ) = 760 mg/kg ( Rat )	= 1370 mg/kg ( Rabbit ) = 790 mg/kg ( Rabbit )	= 1224 ppm ( Rat ) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg ( Rat )	N/A	N/A
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
1,3,5-TRIMETHYLBENZENE 108-67-8	N/A	N/A	= 24 g/m <sup>3</sup> ( Rat ) 4 h
ETHYL ALCOHOL 64-17-5	= 7060 mg/kg ( Rat )	N/A	= 124.7 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**MUTAGENIC EFFECTS** No information available.

**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	N/A	X
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
ETHYL ALCOHOL 64-17-5	A3	Group 1	Known	X

**Legend:**

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive Toxicity** No information available.

**Specific target organ systemic toxicity (single exposure)** No information available.

**Specific target organ systemic toxicity (repeated exposure)** No information available.

**Target Organ Effects** Central nervous system (CNS), Eyes, Lungs, Lymphatic System, Peripheral Nervous System (PNS), Respiratory system, Skin.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1216 mg/kg

ATEmix (dermal) 8489 mg/kg

ATEmix (inhalation-dust/mist) 4.6 mg/l

Oral LD50 2072 mg/kg (rat) Estimated

Dermal LD50 13106 mg/kg (rat) Estimated

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static	N/A
METHYL ETHYL KETONE 78-93-3	N/A	3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	4025 - 6440: 48 h Daphnia magna mg/L EC50 Static 5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50
ACETYLACETONE 123-54-6	N/A	50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50	34.4: 48 h Daphnia magna mg/L EC50

		flow-through 98.3 - 110: 96 h Pimephales promelas mg/L LC50 flow-through	
1,2,4-TRIMETHYLBENZENE 95-63-6	N/A	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
1,3,5-TRIMETHYLBENZENE 108-67-8	N/A	3.48: 96 h Pimephales promelas mg/L LC50	N/A
ETHYL ALCOHOL 64-17-5	N/A	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
METHYL AMYL KETONE 110-43-0	1.98
BUTYL ACETATE 123-86-4	1.81
METHYL ETHYL KETONE 78-93-3	0.3
ACETYLACETONE 123-54-6	0.34
LIGHT STABILIZER 41556-26-7	0.37
ETHYL ALCOHOL 64-17-5	-0.32

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Waste treatment methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number**

D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
METHYL ETHYL KETONE 78-93-3	Included in waste streams: F005, F039	200.0 mg/L regulatory level

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
BUTYL ACETATE 123-86-4	Toxic
METHYL ETHYL KETONE 78-93-3	Toxic mixture of acetone, methyl acetate, and methyl alcohol Ignitable mixture of acetone, methyl acetate, and methyl alcohol
ETHYL ALCOHOL 64-17-5	Toxic Ignitable

**14. TRANSPORT INFORMATION****DOT**

UN-No

UN1263

<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Special Provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Description</b>	UN1263, Paint, 3, II
<b>Emergency Response Guide Number</b>	128

**TDG**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263, Paint, 3, II

**MEX**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263, Paint, 3, II

**ICAO**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Special Provisions</b>	A3, A72
<b>Description</b>	UN1263, Paint, 3, II

**IATA**

<b>UN-No</b>	UN1263
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>ERG Code</b>	3L
<b>Special Provisions</b>	A3, A72, A192

**IMDG/IMO**

<b>UN-No</b>	UN1263
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>EmS-No</b>	F-E, S-E
<b>Special Provisions</b>	163, 367

**RID**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1
<b>Description</b>	UN1263, Paint, 3, II

**ADR/RID**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard class</b>	3
<b>Packing Group</b>	II
<b>Classification Code</b>	F1
<b>Tunnel restriction code</b>	(D/E)
<b>Special Provisions</b>	163, 640C, 650, 367
<b>Description</b>	UN1263, Paint, 3, II, (D/E)
<b>ADR/RID-Labels</b>	3



**ADN**

**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II  
**Hazard Labels** 3  
**Limited Quantity (LQ)** 5 L  
**Ventilation** VE01

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

**Acute Health Hazard** No  
**Chronic Health Hazard** No  
**Fire Hazard** Yes  
**Sudden Release of Pressure Hazard** No  
**Reactive Hazard** No

**CAA (Clean Air Act)**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
BUTYL ACETATE	5000 lb	N/A	N/A	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ETHYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

**State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
CARBON BLACK	1333-86-4	Carcinogen
TITANIUM DIOXIDE	13463-67-7	Carcinogen
ETHYL ALCOHOL	64-17-5	Carcinogen Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL AMYL KETONE	X	X	X	N/A	N/A
BUTYL ACETATE	X	X	X	N/A	N/A
METHYL ETHYL KETONE	X	X	X	X	N/A
ZINC PHOSPHATE	N/A	X	X	N/A	N/A
CARBON BLACK	X	X	X	X	X
ACETYLACETONE	X	X	X	N/A	N/A
TITANIUM DIOXIDE	X	X	X	N/A	N/A
BUTYL ALCOHOL	X	X	X	N/A	N/A
ETHYL ALCOHOL	X	X	X	X	N/A
N-PROPYLBENZENE	X	X	X	N/A	N/A

**International Regulations****Mexico - Grade**

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm
BUTYL ACETATE	N/A	Mexico: TWA 150 ppm Mexico: TWA 710 mg/m <sup>3</sup> Mexico: STEL 200 ppm
METHYL ETHYL KETONE	N/A	Mexico: TWA 200 ppm Mexico: STEL 300 ppm
CARBON BLACK	A3	Mexico: TWA 3 mg/m <sup>3</sup>
ACETYLACETONE	N/A	Mexico: TWA 20 ppm
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m <sup>3</sup>
ETHYL ALCOHOL	A3	Mexico: STEL 1000 ppm

**16. OTHER INFORMATION****NFPA**

Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical Hazards -

NFPA Rating



**HMIS**                      **Health Hazard 1 \***   **Flammability 3**                      **Physical Hazard 0**   **Personal protection X**

*Chronic Hazard Star Legend*

*\* Chronic Health Hazard*

**Issuing Date:**                      23-Jan-2024

**Revision Date:**                      23-Jan-2024

**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. WCS007UZ

**end**